SYSTEMY AN-KOM ODGROMOWE

KARTA DANYCH TECHNICZNYCH

Accessories roof adhesive mass **N828540**



WERSJA MATERIAŁOWA:

OPIS:
The adhesive mass is used for gluing plastic holders to roofing felt.
Substrate and ambient temperature during application and bonding: from +5°C to +25°C
Drying time: 24h
Method of application:
1. Thoroughly mix the content of the bucket.
2. Apply a small amount of glue to the holder with a spatula and the place where holder should be glued using the "glue to glue" method.
3. Wait 20 minutes.
4. Place the holder and press it against the roofing.
Properties:
modified SBS,
has excellent adhesive properties,
has very good adhesion to the roofing felt,
resistant to weather conditions, high and low temperatures,
resistant to short and long-term aging,
easy and quick to use
!!! CAUTION!!!
Do not use to cover PVC, EPDM membranes.

symbol typ	**N828540** AN-MK-1
weight (kg)	
usage	
klasa odporności prądowej	-

AN-KOM 2 Sp. z o.o.
Inwałd, ul. ks. Władysława Bukowińskiego 15
34-120 Andrychów

www.an-kom.pl
biuro@an-kom.pl

tel./fax
+48 33 875 18 11
+48 33 870 60 88